

*Labels from nature*



## ECO.BIO.S100

### Thermal Eco paper – BioTAK® S100

#### Facestock

A white thermal (eco) sensitive paper

Thickness: 82µm (3,22 mil)  
Yield: 75 g/m<sup>2</sup> (107 lbs/mmsi)  
51# per ream (25"X38")

---

#### Liner

The liner is a white glassine paper

Thickness: 54µm (2,13 mil)  
Yield: 61 g/m<sup>2</sup> (88 lbs/mmsi)  
39# per ream (24"X36")

#### Applications

The product is specifically suited for applications where the complete packaging should be compostable.

The self-adhesive label complies EN13432 and EU food regulation for direct food contact.

For all applications we recommend to test the performance of the labels.

#### Reel specifications

Reel lengths 1.000 and 2.000m, standard width of 250mm, 333mm and 500mm on 76mm (3") core. Other dimensions available on request.

#### Adhesive

BioTAK® S100 is a permanent compostable acrylic adhesive. It is carefully formulated to include a high content of renewable materials.

The adhesive is certified to EN13432 and complies EC 1935/2004 & FDA (175.105) for direct food applications.

The adhesive is permanently tacky, having a good initial tack and adheres on a wide variety of substrates.

**BioTAK**

