



## NVLC.S100 NatureFlex™ transparent - BioTAK® S100

### Facestock

NatureFlex™ is a coated transparent high gloss film for labelling applications, produced from wood pulp.

Certified compostable both in industrial and home compostable environments and suitable for anaerobic digestion.

Thickness: 45µm (1.90 mil)  
Yield: 64,5 g/m<sup>2</sup> (93 lbs/mmsi)  
54# per ream (25" \* 38")

### Liner

The liner is a white glassine paper

Thickness: 54µm (2,13 mil)  
Yield: 61 g/m<sup>2</sup> (88 lbs/mmsi)  
39# per ream (24" \* 36")

grease. The labels is suitable for applications to complete biobased and biodegradable packaging.

Facestock and adhesive are certified for direct food applications(fruitlabeling).

For all applications we recommend to test the performance of the labels.

### Adhesive

BioTAK® S100 is a permanent compostable acrylic adhesive. It is carefully formulated to include a high content of renewable materials.

The adhesive is certified to EN13432 and complies EC1935/2004 & FDA (175.105) for direct food applications.

The adhesive is permanently tacky, having a good initial tack and adheres on a wide variety of substrates

### Applications

The product is suitable for a variety of applications. The label is resistant to oil and

#### Reel specifications

Reel lengths 1.000 and 2.000m, standard width of 250mm, 333mm and 500mm on 76mm (3") core. Other dimensions available on request.