



W504V.S100
NatureFlex™ white -
BioTAK® S100

Facestock

NatureFlex™ is a coated white high gloss film for labelling applications, produced from wood pulp.

Certified compostable both in industrial and home compostable environments and suitable with anaerobic digestion.

Thickness: 42µm (1,77 mil)
Yield: 64,5 g/m² (10,900 in²/lb)
54# per ream (25" * 38")

Liner

The liner is a white glassine paper

Thickness: 54µm (2,13 mil)
Yield: 61 g/m² (88 lbs/mmsi)
39# per ream (24" * 36")

and adhesive are certified for direct food applications (fruit labeling).

For all applications we recommend to test the performance of the labels.

Adhesive

BioTAK® S100 is a permanent compostable acrylic adhesive. It is carefully formulated to include a high content of renewable materials.

The adhesive is certified to EN13432 and complies EC1935/2004 & FDA (175.105) for direct food applications.

The adhesive is permanently tacky, having a good initial tack and adheres on a wide variety of substrates

Applications

The product is suitable for a variety of applications. The labels is resistant to oil and grease. The label is very suitable for applications to complete a biodegradable packaging. Facestock

Reel specifications

Reel lengths 1.000 and 2.000m, standard width of 250mm, 333mm and 500mm on 76mm (3") core. Other dimensions available on request.