

PRODUCT DATA SHEET

NatureFlex™ White - BioTAK® S100

NFW.S100



FACESTOCK

DESCRIPTION	NatureFlex™ White is a coated white high gloss film, made from cellulose derived from wood pulp, carrying FSCTM and PEFC certifications
THICKNESS	42 µm
YIELD	64,5 g/m ²

ADHESIVE - BIOTAK®

DESCRIPTION	BioTAK® is a permanent acrylic adhesive
TACK	12.5N/25mm FTM 9 Glass
PEEL ADHESION 90°	7N/25mm FTM 2 St.St.
MIN. APPL. TEMP.	5°C
SERVICE TEMP.	-20°C to 80°C



LINER

DESCRIPTION	The liner is a white glassine paper
THICKNESS	55 µm
YIELD	62 g/m ²

ABOUT

TOTAL CALIPER	117 µm ± 10%
PRINTING	Printable by conventional as well as digital printing techniques. Matt lacquer can be used for a less glossy appearance.
APPROVALS	Facestock and adhesive are certified compostable, compliant to EN13432 For direct food application in compliance with EC1935/2004 & FDA 175.105
STORAGE CONDITIONS	Storage at a temperature of 20 ± 5°C, a relative humidity of 45 ± 5 % is recommended. Moisture, heat and direct sunlight must be avoided.
SHELF LIFE	The shelf life is up to 1 year from date of production.
APPLICATIONS	The material is very suitable to complete a biodegradable packaging. It is resistant to oil and greases. As the facestock is semi-permeable to moisture we recommend testing the performance of the material for all applications.

Disclaimer: All technical information and recommendations are based on our knowledge and experience of the product but do not constitute a warranty or guarantee. Although we make every effort to ensure that all information is correct, we accept no liability for any errors or omissions. The content of this document is given for information purposes only and does not provide any guarantee or warranty that the product is suitable for the client's specific use.

Version 07.22