

PRODUCT DATA SHEET

Vibers™ - BioTAK® XS102

VIB90.XS102



FACESTOCK

DESCRIPTION	An FSC® certified paper made of Elephant grass sourced from fallow Dutch soil and FSC® certified mixed cellulose; unbleached and uncoated, fibers still visible
THICKNESS	120 µm
YIELD	90 g/m2

ADHESIVE - BIOTAK®



DESCRIPTION	BioTAK® is a permanent acrylic adhesive
TACK	12.5N/25mm FTM 9 Glass
PEEL ADHESION 90°	7N/25mm FTM 2 St.St.
MIN. APPL. TEMP.	5°C
SERVICE TEMP.	-20°C to 80°C

LINER

DESCRIPTION	The liner is a white glassine paper
THICKNESS	55 µm
YIELD	62 g/m2

ABOUT

TOTAL CALIPER	185 µm ± 10%
PRINTING	Printable by conventional as well as digital printing techniques. The material is a premium quality paper with a vibrant and fresh look and feel.
APPROVALS	Adhesive is certified compostable, compliant to EN13432 For direct food application in compliance with EC1935/2004 & FDA 175.105
STORAGE CONDITIONS	Storage at a temperature of 20 ± 5°C, a relative humidity of 45 ± 5 % is recommended. Moisture, heat and direct sunlight must be avoided.
SHELF LIFE	The shelf life is up to 1 year from date of production.
APPLICATIONS	The material is a sustainable alternative to conventional paper labels. For all applications we recommend testing the performance of the material.

Disclaimer: All technical information and recommendations are based on our knowledge and experience of the product but do not constitute a warranty or guarantee. Although we make every effort to ensure that all information is correct, we accept no liability for any errors or omissions. The content of this document is given for information purposes only and does not provide any guarantee or warranty that the product is suitable for the client's specific use.

Version 07.22