

Product Datasheet
 Machine Coated paper - BioTAK® S100
 MC80.S100



Facestock

Description	A white paper, made from FSC® certified pulp, one side (semi-gloss) coated
Thickness	70 µm
Yield	80 g/m ²

Adhesive - BioTAK®

Description	BioTAK® is a permanent acrylic adhesive
Tack	12.5N/25mm FTM 9 Glass
Peel Adhesion 90°	7N/ 25mm FTM 2 St.St.
Min. Appl. Temp.	5°C
Service Temp.	-20°C to 80°C



Liner

Description	The liner is a white glassine paper
Thickness	55 µm
Yield	62 g/m ²

About

Total Caliper	135 µm ± 10%
Printing	Printable by conventional as well as digital printing techniques. Ideal for sharp printing; additional varnish possible (like high gloss, TT-varnish).
Approvals	Facestock and adhesive are certified compostable, compliant to EN13432 For direct food application in compliance with EC1935/2004 & FDA 175.105
Storage conditions	Storage at a temperature of 20 ± 5°C, a relative humidity of 45 ± 5 % is recommended. Moisture, heat and direct sunlight must be avoided.
Shelf life	The shelf life is up to 1 year from date of production.
Applications	The material is very suitable to complete a biodegradable packaging. For all applications we recommend testing the performance of the material.

Bio4life B.V. - Venkelbaan 82 - 2908 KE - Capelle a/d IJssel (NL) - sales@bio4life.nl

Disclaimer: All technical information and recommendations are based on our knowledge and experience of the product but do not constitute a warranty or guarantee. Although we make every effort to ensure that all information is correct, we accept no liability for any errors or omissions. The content of this document is given for information purposes only and does not provide any guarantee or warranty that the product is suitable for the client's specific use.